


Ocean LED light/ Foco Ocean

The **Ocean submersible LED light** is the result of our constant search of the excellence. Lighting available in 36W LED High performance, optional RGB and WHITE, also 10° or 30° lenses, IP 68 connector included. Manufactured in brass and Stainless Steel AISI-304, **new slim design, is strong and very light, IP68 certified.** High heat dissipation, thanks to the large contact area.

El **foco LED sumergible Ocean** es el resultado de nuestra continua búsqueda de la excelencia. Iluminación disponible en 36W de potencia LED de alto rendimiento y opcional RGB, BLANCO, y ópticas 10° o 30°, conector incluido. Fabricado en Latón y Acero Inoxidable AISI-304, **diseño extraplano, es un foco robusto, muy ligero y certificado IP 68.** Alta disipación de calor, gracias a la gran superficie de contacto.



Certifications/ Certificaciones **IP68 CE**



Light charts/ Gráficos de iluminación.

Spot/ Intensivo (Beam 10°)					Flood/ Extensivo (Beam 30°)				
Color	White/ Blanco		RGB		Color	White		RGB	
Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro
1 m	Ø 0,24	16808 lx	Ø 0,21	12063 lx	1 m	Ø 0,34	10171 lx	Ø 0,30	6095 lx
2 m	Ø 0,48	4202 lx	Ø 0,42	3016 lx	2 m	Ø 0,68	2543 lx	Ø 0,59	1524 lx
3 m	Ø 0,73	1867 lx	Ø 0,63	1340 lx	3 m	Ø 1,03	1130 lx	Ø 0,89	677 lx
4 m	Ø 0,97	1050 lx	Ø 0,84	754 lx	4 m	Ø 1,37	636 lx	Ø 1,19	381 lx
5 m	Ø 1,21	672 lx	Ø 1,05	482 lx	5 m	Ø 1,71	407 lx	Ø 1,49	244 lx
7 m									
9 m									

Electrical data/ Datos eléctricos								Details/ Detalles		
Reference/ Referencia	Power/ Potencia	Voltage/ Voltaje	Beam an- gle/ Ángulo	Color/ Color	LEDs Num./ Nº de LEDs	Lumens/ Lúmens	Life span/ Vida útil	Material/ Material	Weight/ Peso	Elect. connection/ Conexión eléctrica
F5220202	36 W	24V DC	10°	White 6500K	12	1486 lm	40000/hrs	STAINLESS STEEL AISI-304 - BRASS/ ACERO INOXIDABLE AISI-304 - LATÓN	1,63 kg	Plug & Socket / Conector enchufable IP68 Connector H05RR-F/ H05RN-F H07RR-F/H07RN-F Ø 7 - Ø12
F5220213			30°			1524 lm				
F5225207			10°	702,9 lm						
F5225218			30°	702,3 lm						