

Ocean LED light/ Foco Ocean

The Ocean submersible LED light is the result of our constant search of the excellence. Lighting available in 36W LED High performance, optional RGB, RGBW and WHITE, also 10° or 30° lenses, IP 68 connector included. Manufactured in brass and Stainless Steel AISI-304, new slim design, is strong and very light, IP68 certified. High heat dissipation, thanks to the large contact area.

El foco LED sumergible Ocean es el resultado de nuestra continua búsqueda de la excelencia. Iluminación disponible en 36W de potencia LED de alto rendimiento y opcional RGB, RGBW, BLANCO, y ópticas 10° o 30°, conector incluido. Fabricado en Latón y Acero Inoxidable AISI-304, diseño extraplano, es un foco robusto, muy ligero y certificado IP 68. Alta disipación de calor, gracias a la gran superficie de contacto.



Certifications/ Certificaciones

IP68 CE

AISI 304

DETACH

LED




RGB

RGBW

PLC + HMI

PWM



Light charts/ Gráficos de iluminación.

Spot/ Intensivo (Beam 10°)							Flood/ Extensivo (Beam 30°)						
Color	250 RGB		500 White/ Blanco		750 RGBW		Color	250 RGB		500 White/ Blanco		750 RGBW	
Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro
1 m	Ø 0,18	12063 lx	Ø 0,22	16808 lx	Ø 0,20	13428 lx	1 m	Ø 0,51	6095 lx	Ø 0,54	10171 lx	Ø 0,53	9336 lx
2 m	Ø 0,36	3016 lx	Ø 0,42	4202 lx	Ø 0,39	3357 lx	2 m	Ø 0,99	1524 lx	Ø 1,06	2543 lx	Ø 1,02	2334 lx
3 m	Ø 0,52	1340 lx	Ø 0,60	1867 lx	Ø 0,55	1492 lx	3 m	Ø 1,44	677 lx	Ø 1,56	1130 lx	Ø 1,50	1037 lx
4 m	Ø 0,70	754 lx	Ø 0,81	1050 lx	Ø 0,74	839 lx	4 m	Ø 2,02	381 lx	Ø 2,11	636 lx	Ø 2,09	583 lx
5 m	Ø 0,87	482 lx	Ø 0,97	672 lx	Ø 0,92	537 lx	5 m	Ø 2,57	244 lx	Ø 2,64	407 lx	Ø 2,59	373 lx
6 m					Ø 1,07	373 lx	6 m					Ø 3,18	259 lx

Lighting/
Iluminación

Electrical data/ Datos eléctricos									Details/ Detalles			
Reference/ Referencia	Model/ Modelo	Power/ Potencia	Voltage/ Voltaje	Beam angle/ Ángulo	Color/ Color	LEDs Num./ Nº de LEDs	Lumens/ Lúmens	Life span/ Vida útil	Material/ Material	Weight/ Peso	Elect. connection/ Conexión eléctrica	
F5225231	250	20 W	24V DC	10°	RGB	12	930 lm	40000/hrs	STAINLESS STEEL AISI-304 - BRASS/ ACERO INOXIDABLE AISI-304 - LATÓN	1,63 kg	Plug & Socket / Conector enchufable IP68 Connector H05RR-F/ H05RN-F H07RR-F/H07RN-F Ø 7 - Ø12	
F5225242				30°			930 lm					
F5220202	500	36 W		10°	White 6500K		1524 lm					
F5220213				30°			1524 lm					
F5216218	750	36 W		10°	RGBW	14	2448 lm					
F5216229				30°			2448 lm					3m H07RN-F 5G1mm ²

Further information at www.saferain.com | Más información en www.saferain.com